

**Rychlospojky Soft-Flow, DN 41**

z nerezové oceli 1.4305

**LÜDECKE**

2

Vsušky s trnem na hadici						
Obj. č.	Trn na hadici	l	d	Délka trnu	Světlost	Hmotnost (g)
GRS38T	38 mm	83	55	45	34	310
GRS40T	40 mm	83	55	45	36	315
GRS45T	45 mm	83	55	45	41	330
GRS50T	50 mm	83	55	45	41	360



Vsušky pro připojení na trubky					
Obj. č.	Vnější průměr trubky	l	d	Světlost	Hmotnost (g)
GRS38R	38 mm	68,5	58	34	360
GRS40R	40 mm	68,5	58	36	370
GRS45R	45 mm	68,5	58	41	385
GRS50R	50 mm	68,5	58	41	420



Vsušky s vnitřním závitem					
Obj. č.	Závít	l	d	Světlost	Hmotnost (g)
GRS15I	G 1 1/2"	65	59	41	350
GRS20I	G 2"	65	59	41	380



Zaslepovací vsušky s řetízku					
Obj. č.	Materiál	l	d	Délka řetízku	Hmotnost (g)
GRS-V	nerezová ocel	60	58	170	195



## související zboží:

PVC hadice  
str. 478Sací hadice  
str. 512Válce  
str. 810Ventily  
str. 869