

Šroubení pro potravinářství

dle normy DIN 11851

NEREZ

Vsušky s drážkovaným trnem				
Obj. č.	Trn na hadici	DN	Materiál	Hmotnost (kg)
DKVSR-013	13 mm	15	nerez AISI 316	0,05
DKVSR-019	19 mm	20	nerez AISI 316	0,10
DKVSR-025	25 mm	25	nerez AISI 316	0,17
DKVSR-032	32 mm	32	nerez AISI 316	0,24
DKVSR-038	38 mm	38	nerez AISI 316	0,32
DKVSR-050	50 mm	50	nerez AISI 316	0,47
DKVSR-063	63 mm	63	nerez AISI 316	0,78
DKVSR-075	75 mm	80	nerez AISI 316	1,08
DKVSR-100	100 mm	100	nerez AISI 316	1,90



Vsušky s návarkem					
Obj. č.	DN	Průměr kónusu	Průměr návarku		Hmotnost (kg)
			vnější	vnitřní	
DIN214-015	15	28	21	16	0,03
DIN214-020	20	36	25	20	0,05
DIN214-025	25	44	31	26	0,09
DIN214-032	32	50	37	32	0,12
DIN214-040	40	56	43	38	0,14
DIN214-050	50	68	55	50	0,19
DIN214-065	65	86	72	66	0,32
DIN214-080	80	100	87	81	0,39
DIN214-100	100	121	106	100	0,62



Zaslepovací vsušky					
Obj. č.	DN	Závit	Vněj. průměr	Výška	Hmotnost (kg)
DIN220-015	15	Rd 34 × 1/8"	44	18	0,10
DIN220-020	20	Rd 44 × 1/6"	54	21	0,14
DIN220-025	25	Rd 52 × 1/6"	63	21	0,33
DIN220-032	32	Rd 58 × 1/6"	70	21	0,41
DIN220-040	40	Rd 65 × 1/6"	78	21	0,49
DIN220-050	50	Rd 78 × 1/6"	92	22	0,71
DIN220-065	65	Rd 95 × 1/6"	112	25	1,24
DIN220-080	80	Rd 110 × 1/4"	127	30	1,75
DIN220-100	100	Rd 130 × 1/4"	148	31	2,43



Zaslepovací vsušky s kolíkem					
Obj. č.	DN	Závit	Vněj. průměr	Výška	Hmotnost (kg)
DIN221-015	15	Rd 34 × 1/8"	44	18	0,15
DIN221-020	20	Rd 44 × 1/6"	54	21	0,23
DIN221-025	25	Rd 52 × 1/6"	63	21	0,33
DIN221-032	32	Rd 58 × 1/6"	70	21	0,41
DIN221-040	40	Rd 65 × 1/6"	78	21	0,49
DIN221-050	50	Rd 78 × 1/6"	92	22	0,71
DIN221-065	65	Rd 95 × 1/6"	112	25	1,24
DIN221-080	80	Rd 110 × 1/4"	127	30	1,75
DIN221-100	100	Rd 130 × 1/4"	148	31	2,43

