

Koncovky Global Spiral



se závity JIC 37°

Kolena 90°, dlouhé provedení, s vnitřním závitem JIC 37°, s o-kroužkem, otočná							
Obj. č.	Hadice D DN	Závit JIC 37°	A (mm)	B (mm)	E (mm)	H1 (mm)	H2 (mm)
GJ-F90L-91610	10 mm	UNF 9/16"-18	86,0	50,2	54,0	19,1	19,1
GJ-F90L-3412	12 mm	UNF 3/4"-16	92,0	54,6	64,0	22,2	22,2
GJ-F90L-7812	12 mm	UNF 7/8"-14	89,0	51,5	70,0	27,0	22,2
GJ-F90L-171620	20 mm	UN 1 1/16"-12	113,0	62,0	96,0	31,8	28,6
GJ-F90L-211625	25 mm	UN 1 5/16"-12	144,0	87,6	114,0	38,1	38,1
GJ-F90L-13825	25 mm	UN 1 5/8"-12	154,0	97,6	129,0	50,8	38,1
GJ-F90L-13832	32 mm	UN 1 5/8"-12	174,0	102,9	129,0	50,8	47,6

Poznámka: pro rozměry 10 až 32 mm je pracovní tlak 420 bar

Koncovky s vnějším závitem JIC 37°					
Obj. č.	Hadice D DN	Závit JIC 37°	A (mm)	B (mm)	H (mm)
GJ-M-91610	10 mm	UNF 9/16"-18	66,0	30,2	17,5
GJ-M-3410	10 mm	UNF 3/4"-16	70,0	34,2	20,6
GJ-M-7810	10 mm	UNF 7/8"-14	77,0	41,2	23,8
GJ-M-3412	12 mm	UNF 3/4"-16	72,0	34,5	20,6
GJ-M-7812	12 mm	UNF 7/8"-14	75,0	37,5	22,2
GJ-M-7816	16 mm	UNF 7/8"-14	92,0	41,7	23,8
GJ-M-171616	16 mm	UN 1 1/16"-12	94,0	43,7	27,0
GJ-M-171620	20 mm	UN 1 1/16"-12	93,0	42,0	28,6
GJ-M-191620	20 mm	UN 1 3/16"-12	94,0	43,0	31,8
GJ-M-211620	20 mm	UN 1 5/16"-12	96,0	45,0	33,3
GJ-M-211625	25 mm	UN 1 5/16"-12	104,0	47,2	34,9
GJ-M-13825	25 mm	UN 1 5/8"-12	108,5	51,7	44,5
GJ-M-13832	32 mm	UN 1 5/8"-12	125,0	53,9	44,5
GJ-M-15840	40 mm	UN 1 7/8"-12	130,0	56,4	50,0
GJ-M-2550	50 mm	UN 2 1/2"-12	161,1	69,1	65,0

Poznámka: pro rozměry 10 až 32 mm je pracovní tlak 420 bar



související zboží:

Manometry
str. 625



Hydraulické trubky
str. 410



Rychlospojky
str. 407



Hadice
str. 342

