


Hydraulická šroubení


úhlová šroubení

3



Přepážková I-šroubení										
Obj. č.		Řada	Tlak PN (bar)		Trubka D1	Závit M	Délka L3	Výška L2	SW S1	SW S2
ocel	nerez		ocel	nerez						
L-6L	LX-6L	L	500	315	6 mm	M12 × 1,5	42	27	14	12
L-8L	LX-8L	L	500	315	8 mm	M14 × 1,5	42	29	17	12
L-10L	LX-10L	L	500	315	10 mm	M16 × 1,5	43	30	19	14
L-12L	LX-12L	L	400	315	12 mm	M18 × 1,5	44	32	22	17
L-15L	LX-15L	L	400	315	15 mm	M22 × 1,5	46	36	27	19
L-18L	LX-18L	L	400	315	18 mm	M26 × 1,5	49	40	32	24
L-22L	LX-22L	L	250	160	22 mm	M30 × 2	51	44	36	27
L-28L	LX-28L	L	250	160	28 mm	M36 × 2	52	47	41	36
L-35L	LX-35L	L	250	160	35 mm	M45 × 2	58	56	50	41
L-42L	LX-42L	L	250	160	42 mm	M52 × 2	59	63	60	50
L-6S	-	S	800	-	6 mm	M14 × 1,5	44	31	17	12
L-8S	LX-8S	S	800	630	8 mm	M16 × 1,5	44	32	19	14
L-10S	LX-10S	S	800	630	10 mm	M18 × 1,5	46	34	22	17
L-12S	LX-12S	S	630	630	12 mm	M20 × 1,5	47	38	24	17
L-14S	LX-14S	S	630	630	14 mm	M22 × 1,5	50	40	27	19
L-16S	LX-16S	S	630	400	16 mm	M24 × 1,5	50	43	30	24
L-20S	LX-20S	S	400	400	20 mm	M30 × 2	55	48	36	27
L-25S	LX-25S	S	400	400	25 mm	M36 × 2	59	54	46	36
L-30S	LX-30S	S	400	400	30 mm	M42 × 2	64	62	50	41
L-38S	-	S	400	-	38 mm	M52 × 2	68	72	60	50

Upozornění: pro objednání těla šroubení bez matice a řezného kroužku uveďte na začátek obj.č. písmeno X, např. XL-6L



Kolena s vnitřním metrickým závitem, nastavitelná										
Obj. č.		Řada	Tlak PN (bar)		Závit d1	Trubka D	Délka L2	Výška L5	SW S1	SW S2
ocel	nerez		ocel	nerez						
VB-6L	VBX-6L	L	500	315	M12 × 1,5	6 mm	27	26	14	12
VB-8L	VBX-8L	L	500	315	M14 × 1,5	8 mm	29	27,5	17	12
VB-10L	VBX-10L	L	500	315	M16 × 1,5	10 mm	30	29	19	14
VB-12L	VBX-12L	L	400	315	M18 × 1,5	12 mm	32	29,5	22	17
VB-15L	VBX-15L	L	400	315	M22 × 1,5	15 mm	36	32,5	27	19
VB-18L	VBX-18L	L	400	315	M26 × 1,5	18 mm	40	35,5	32	24
VB-22L	VBX-22L	L	250	160	M30 × 2	22 mm	44	38,5	36	27
VB-28L	VBX-28L	L	250	160	M36 × 2	28 mm	47	41,5	41	36
VB-35L	VBX-35L	L	250	160	M45 × 2	35 mm	56	51	50	41
VB-42L	VBX-42L	L	250	160	M52 × 2	42 mm	63	56	60	50
VB-6S	VBX-6S	S	800	630	M14 × 1,5	6 mm	31	27	17	12
VB-8S	VBX-8S	S	800	630	M16 × 1,5	8 mm	32	27,5	19	14
VB-10S	VBX-10S	S	800	630	M18 × 1,5	10 mm	34	30	22	17
VB-12S	VBX-12S	S	630	630	M20 × 1,5	12 mm	38	31	24	17
VB-14S	-	S	630	-	M22 × 1,5	14 mm	40	35	27	19
VB-16S	VBX-16S	S	630	400	M24 × 1,5	16 mm	43	36,5	30	24
VB-20S	VBX-20S	S	400	400	M30 × 2	20 mm	48	44,5	36	27
VB-25S	-	S	400	-	M36 × 2	25 mm	54	50	46	36
VB-30S	VBX-30S	S	400	400	M42 × 2	30 mm	62	55	50	41
VB-38S	-	S	400	-	M52 × 2	38 mm	72	63	60	50

Upozornění: pro objednání samostatného těla šroubení uveďte na začátek obj.č. písmeno X, např. XVB-6L

související zboží:

Hadice
str. 342



Rychlospojky
str. 407



Nástrčné spojky
str. 38



Manometry
str. 625

